

# SG Series

## Technical specification

<b>General data</b>						
System power range	10 – 40 kVA	60 – 80 kVA	100 – 120 kVA	160 kVA	200 – 300 kVA	400 – 500 kVA
Active power / frame	10/15/20/30/ 40 kW	54 / 72 kW	90 / 108 kW	144 kW	180/ 225 / 270 kW	360 / 450 kW
Output power factor	0.9 lead – 0.6 lag					
Topology	Online double conversion					
UPS type	Standalone, transformer-based					
Parallel configuration	Up to 6 units in parallel with Redundant Parallel Architecture (RPA)					
<b>Input</b>						
Nominal input voltage	3 x 380/400/415 V + N					
Voltage tolerance	340-460 V					
Input distortion THDi	<3%					
Frequency	50/60 Hz					
Frequency range	45-66 Hz					
Power factor	>0.99					
Walk-in / soft start	Yes					
<b>Output</b>						
Rated output voltage	3 x 380/400/415 V + N					
Voltage tolerance	+/-1% static, +/-3% dynamic, +/-3% unbalanced load					
Voltage distortion THDU	<2% linear load, <3% nonlinear load (EN 62040)					
Frequency	50/60 Hz					
Overload capability	150% 1 min, 125% 10 min					
Output short circuit capability	2.7*In(Ph-N) / 4*In(Ph-Ph) for 200 ms					
Crest factor	<3:1					
<b>Efficiency</b>						
Overall efficiency	Up to 92.3%	Up to 91.9%	Up to 92.1%	Up to 94.2%	Up to 94.6%	Up to 94.2%
In eco-mode (eBoost) configuration	Up to 98%	Up to 97.9%	Up to 97.9%	Up to 98.4%	Up to 98.5%	Up to 98.7%
<b>Environment</b>						
Storage temperature	UPS: -25 °C +55 °C					
Operating temperature	0-40 °C					
Humidity	Max. 95% (non-condensing)					
Altitude configuration	Up to 1000 m with no derating, at 1500 m:-2.5%/ 2000 m:-5%/ 2500 m:-7.5%/ 3000 m:-10% (EN/IEC 62040-3)					
<b>Communications</b>						
HMI	Multilingual graphic display (LCD)					
Relay contractors	6 voltage-free contacts for 27 programmable alarms					
Input signals	EPO, Gen-ON (emergency power supply ON, n/o contact), 1 auxiliary signal (settable functionality)					
Communication ports	RS232, SNMP (Modbus IP, RS232, RS485 & BacNet IP)					
<b>Electrical / Mechanical</b>						
Degree of protection	IP20					
Color	10-120 kVA RAL 9003 (white), 160-500 kVA RAL 9005 (black)					
Cable entry	Bottom (top optional)					
Back-feed protection	Built-in as standard					
Serviceability	Fully front serviceable					
Ventilation	From front to top					
Audible noise	<65 dB(A)	63 dB(A)	63 dB(A)	69 dB(A)	69 dB(A)	69 dB(A)
<b>Batteries</b>						
Type	VRLA batteries, vented lead-acid batteries, wet batteries, NiCd, flywheel					
DC floating voltage	409-436 V					
<b>Standards</b>						
Safety	IEC / EN 62040-1					
Electromagnetic compatibility (EMC)	IEC / EN 62040-2					
Performance	IEC / EN 62040-3					
Product certification	CE marking					
Manufacturing	ISO 9001					
<b>Weight, dimensions</b>						
Weight (Kg)	290-420	550-630	860	1050	1220-1560	2190-2470
Dimensions w x h x d (mm)	680x1450x800	650x1900x850	835x1900x850	900x1900x850	1300x1900x850	1800x1900x950